

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
30 November 2000 (30.11.2000)

PCT

(10) International Publication Number
WO 00/72543 A1

- (51) International Patent Classification⁷: **H04L 27/26** (74) Agent: GROENENDAAL, Antonius, W., M.: Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: PCT/EP00/04196
- (22) International Filing Date: 1 May 2000 (01.05.2000) (81) Designated State (*national*): JP.
- (25) Filing Language: English (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- (26) Publication Language: English
- (30) Priority Data: 99201607.1 21 May 1999 (21.05.1999). EP **Published:**
— With international search report.
- (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). *For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*
- (72) Inventor: SCHOUHAMER IMMINK, Kornelis, A.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(54) Title: REDUCTION OF PEAK TO AVERAGE POWER RATIO IN MULTICARRIER TRANSMISSION



(57) Abstract: The transmission system according to the invention comprises a transmitter (10) and a receiver (12). The transmitter (10) can transmit datawords via a multicarrier signal (11) to the receiver (12). In order to reduce the crest factor of this multicarrier signal (11) the transmitter (10) comprises a generator (20) and a selector (22). The generator (20) generates for each dataword (19) a number of alternative sequences (21) by combining mutually different digital words with the dataword (19). For this purpose, the generator (20) may comprise an augmentor (40) and a scrambler (42). The augmentor (40) generates for each dataword (19) a number of intermediate sequences (41) by combining the digital words with the dataword (19). These intermediate sequences (41) are scrambled by the scrambler (42) in order to form the alternative sequences (21). From these alternative sequences (21) the alternative sequence with the lowest peak power value (23) is selected for transmission to the receiver (12).

WO 00/72543 A1

REDUCTION OF PEAK TO AVERAGE POWER RATIO IN MULTICARRIER TRANSMISSION

The invention relates to a transmission system for transmitting datawords via a multicarrier signal from a transmitter to a receiver, the transmitter comprising a generator for generating for each dataword a number of alternative sequences, and the transmitter further comprising a selector for selecting the alternative sequence with the lowest peak power value
5 for transmission to the receiver.

The invention further relates to a transmitter for transmitting datawords via a multicarrier signal to a receiver and a method of transmitting datawords via a multicarrier signal from a transmitter to a receiver.

10

A transmission system according to the preamble is known from WO 98/10567. Multicarrier transmission systems, such as systems employing Orthogonal Frequency Domain Multiplexing (OFDM), enable the transmission of data at a relatively high rate. OFDM, also known as Multicarrier Modulation (MCM) or Discrete MultiTone modulation (DMT), is a
15 technique by which data is transmitted by modulating several low bit rate carriers in parallel, rather than one high bit rate carrier. OFDM is spectrally efficient, and has been shown to be effective for, for example, high performance digital radio links. OFDM is also being used in Digital Subscriber Line systems, e.g. ADSL- or HDSL-systems.

An important characteristic of a multicarrier signal is the crest factor, defined as
20 the ratio of the peak value of an AC waveform to its Root Mean Square (RMS) value. In an OFDM system the crest factor can be high since it is possible for the signals on each of the carriers to be in phase, which gives rise to a relatively high peak value, but on average the phases will be randomly distributed, which gives rise to a much lower mean value. For example, in a 16 carrier OFDM system the peak power can be 16 times the mean transmission
25 power.

As most amplifiers have a limited linear range, the (average) power of the OFDM signal must be made much smaller than that of a typical single-carrier signal in order to prevent clipping. Usually a so-called back-off of 10-12 dB is applied. Clipping of the

OFDM signal results in a decrease of the signal itself, and the distortion manifests itself as additive noise.

In the known transmission system the crest factor is reduced in two steps: first a number of alternative sequences are generated for each dataword, and second the alternative sequence with the lowest peak power value is selected for transmission to the receiver. The alternative sequences are generated by multiplying carrier values, i.e. the multicarrier representation of the datawords, with arbitrarily selected modification vectors.

An object of the invention is to provide a transmission system for transmitting datawords via a multicarrier signal from a transmitter to a receiver, wherein the alternative sequences are generated in a different way. This object is achieved in the transmission system according to the invention, which is characterized in that the generator is embodied so as to combine mutually different digital words with the dataword in order to form the alternative sequences. The digital words can be combined with the dataword simply by placing the digital words in front of the dataword or by placing the dataword in front of the digital words.

A first embodiment of the transmission system according to the invention is characterized in that the generator comprises an augmentor for generating for each dataword a number of intermediate sequences by combining the digital words with the dataword, the generator further comprising a scrambler for scrambling the intermediate sequences in order to form the alternative sequences. The intermediate sequences can be generated by the augmentor simply by placing the digital words in front of the dataword or by placing the dataword in front of the digital words. The inclusion of the mutually different digital words in the intermediate sequences has the effect that the scrambler, which is preferably a self-synchronized scrambler, is initialized for each intermediate sequence with a different digital word. Hence, the alternative sequences are relatively good randomisations of the dataword.

A second embodiment of the transmission system according to the invention is characterized in that the augmentor is embodied so as to generate for each dataword 2^r intermediate sequences by combining all possible digital words of length r with the dataword. In this way a set of alternative sequences is obtained which is optimally randomized.

A third embodiment of the transmission system according to the invention is characterized in that the generator comprises a splitter for splitting the dataword and the digital words into fragments, the generator further comprising a combiner for combining the fragments in order to form the alternative sequences. The combiner generates for each digital

word an alternative sequence by randomly mixing the fragments of that digital word with the fragments of the dataword.

A fourth embodiment of the transmission system according to the invention is characterized in that the selector comprises an Inverse Discrete Fourier Transformer for calculating for each alternative sequence the Inverse Discrete Fourier Transform (IDFT), the selector further comprising means for determining for each alternative sequence the maximum of the calculated IDFT values, the selector also comprising means for selecting the alternative sequence with the lowest maximum for transmission to the receiver. By these measures the alternative sequence with the lowest peak power value can be determined effectively.

The above object and features of the present invention will be more apparent from the following description of the preferred embodiments with reference to the drawings, wherein:

Figure 1 shows a block diagram of an embodiment of a transmission system according to the invention,

Figure 2 shows a block diagram of part of an embodiment of a transmitter according to the invention,

Figure 3 shows a block diagram of a first embodiment of a generator for use in a transmission system according to the invention,

Figure 4 shows a block diagram of a selector for use in a transmission system according to the invention,

Figure 5 shows a block diagram of a second embodiment of a generator for use in a transmission system according to the invention.

Figure 1 shows a block diagram of an embodiment of a transmission system according to the invention. In such a transmission system datawords are transmitted via a multicarrier signal 11 by a transmitter 10 to a receiver 12. The transmission system may comprise further transmitters 10 and receivers 12. The transmitters 10 and the receivers 12 can be of many different types depending on the particular application area. For example, in a Wireless Asynchronous Transfer Mode (WATM) system which supports high speed, short distance radio links between computer systems, a two-way radio communication link could be established between a personal computer and a printer. For this purpose, the personal

computer and the printer are both equipped with a transmitter 10 and a receiver 12.

Alternatively, in a Digital Audio Broadcast (DAB) system the transmitter 10 could be part of a radio broadcast station, while the receiver 12 could be included in a car radio.

Figure 2 shows a block diagram of a part of an OFDM transmitter 10 according to the invention. The part that is shown relates to the encoding of an input bitstream 19 and its modulation for transmission. Operational parameters of all blocks shown are controlled by a controller (not shown). The bitstream 19 comprises datawords 19 to be transmitted, passed from a Medium Access Control (MAC) layer. The datawords 19 are first passed to a generator 20, which generates for each dataword 19 a number of alternative sequences 21. Next, in a selector 22 the alternative sequence with the lowest peak power value 23 is selected for transmission to the receiver 12. This selected alternative sequence 23 is passed to an encoding block 24, which generates a required stream of symbols 25 in an appropriate form for the modulation scheme being used for transmission, for example two bit symbols if Differential Quadrature Phase Shift Keying (DQPSK) is to be used. An interleaver 26 takes this stream of input symbols 25 and outputs each symbol onto a respective one of its parallel output lines 27. Each output line corresponds to an OFDM carrier for transmission, so the number of output lines 27 from the interleaver 26 is the same as the number of carriers. The symbols on each of the output data lines 27 from the interleaver 26 are then modulated by a modulator 28 using the required modulation scheme, for example DQPSK. The modulated data 29 is then inverse discrete Fourier transformed by an IDFT block 30 (or equivalently is inverse fast Fourier transformed), which block also recombines the output data 27 into a serial stream 31. A guard band between OFDM symbols is added by an extender 32, to reduce problems of inter-symbol interference, before the data 33 is passed to a digital to analogue converter 34. The output signal 35 thereof is then passed to radio transmission means 36, which translate it to the required frequency and amplify it for transmission to the receiver 12.

Figure 3 shows a block diagram of a generator 20 for use in a transmission system according to the invention. The generator 20 comprises an augmentor 40 that generates for each dataword 19 a number of intermediate sequences 41 by combining mutually different digital words with the dataword 19. The intermediate sequences 41 can be generated by the augmentor 40 simply by placing the digital words in front of the dataword 19 or by placing the dataword 19 in front of the digital words. The generator 20 further comprises a scrambler 42 that scrambles the intermediate sequences 41 in order to form the alternative sequences 21.

The inclusion of the mutually different digital words in the intermediate sequences 41 has the effect that the scrambler 42, which is preferably a self-synchronized

scrambler, is initialized for each intermediate sequence 41 with a different digital word. Hence, the alternative sequences 21 are relatively good randomisations of the dataword 19.

Preferably the augmentor 40 is embodied so as to generate for each dataword 19 2^r intermediate sequences 41 by combining all possible digital words of length r with the dataword 19. In this way a set of alternative sequences 21 is obtained which is optimally randomized.

Figure 4 shows a block diagram of a selector 22 for use in a transmission system according to the invention. The selector 22 comprises an Inverse Discrete Fourier Transformer 50 that calculates for each alternative sequence 21 the Inverse Discrete Fourier Transform (IDFT). The selector 22 further comprises means 52 that determine for each alternative sequence 21 the maximum of the calculated IDFT values 51. The selector 22 also comprises means 54 that select the alternative sequence 21 with the lowest maximum 23 for transmission to the receiver 12.

For example, if the augmentor 40 is embodied so as to generate the intermediate sequences 41 by placing all digital words of length r in front of the dataword 19, the augmentor 40 generates from a dataword x a set of intermediate sequences $B_x = \{b_1, \dots, b_M\}$, wherein:

$$b_1 = (0, 0, \dots, 0, x_1, \dots, x_m)$$

$$b_2 = (0, 0, \dots, 1, x_1, \dots, x_m)$$

...

$$b_L = (1, 1, \dots, 1, x_1, \dots, x_m)$$

A set of alternative sequences C_x is obtained by scrambling all intermediate sequences in B_x . Let the scrambler polynomial $s(x)$ be denoted by:

$$s(x) = x^s + \sum_{k=1}^s a_k x^{s-k},$$

where s denotes the register length of the scrambler. The scrambler translates each intermediate sequence $b = (b_1, \dots, b_n) \in B_x$ into an alternative sequence

$$c = (c_1, \dots, c_n) = f(b) \in C_x \text{ using the recursion } c_i = b_i + \sum_{k=1}^s a_k c_{i-k}.$$

Next, the alternative sequence in C_x with the lowest peak power value is selected for transmission to the receiver 12. In the receiver 12 the inverse operation

$$b = f^{-1}(c) \text{ has to be performed, using the recursion } b_i = c_i + \sum_{k=1}^s a_k c_{i-k}.$$

Finally, the dataword is found by deleting the first r bits.

Figure 5 shows a block diagram of another generator 20 for use in a transmission system according to the invention. The generator 20 comprises a splitter 60 that splits each dataword 19 and a number of mutually different digital words into fragments 61. These fragments may have mutually different lengths. The generator 20 further comprises a combiner 62 that combines the fragments 61 in order to form the alternative sequences 21. The combiner 62 generates for each digital word an alternative sequence 21 by randomly mixing the fragments of that digital word with the fragments of the dataword 19.

The scope of the invention is not limited to the embodiments. The invention is embodied in each new characteristic and each combination of characteristics. Any reference signs do not limit the scope of the claims. The word "comprising" does not exclude the presence of elements or steps other than those listed in a claim. Use of the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements.

CLAIMS:

1. A transmission system for transmitting datawords via a multicarrier signal (11) from a transmitter (10) to a receiver (12), the transmitter (10) comprising a generator (20) for generating for each dataword (19) a number of alternative sequences (21), and the transmitter (10) further comprising a selector (22) for selecting the alternative sequence with the lowest peak power value (23) for transmission to the receiver (12), characterized in that the generator (20) is embodied so as to combine mutually different digital words with the dataword (19) in order to form the alternative sequences (21).
2. A transmission system according to Claim 1, characterized in that the generator (20) comprises an augmentor (40) for generating for each dataword (19) a number of intermediate sequences (41) by combining the digital words with the dataword (19), the generator (20) further comprising a scrambler (42) for scrambling the intermediate sequences (41) in order to form the alternative sequences (21).
3. A transmission system according to Claim 2, characterized in that the augmentor (40) is embodied so as to generate for each dataword (19) 2^r intermediate sequences (41) by combining all possible digital words of length r with the dataword (19).
4. A transmission system according to Claim 1, characterized in that the generator (20) comprises a splitter (60) for splitting the dataword (19) and the digital words into fragments (61), the generator (20) further comprising a combiner (62) for combining the fragments (61) in order to form the alternative sequences (21).
5. A transmission system according to any one of Claims 1 to 4, characterized in that the selector (22) comprises an Inverse Discrete Fourier Transformer (50) for calculating for each alternative sequence the Inverse Discrete Fourier Transform (IDFT), the selector (22) further comprising means (52) for determining for each alternative sequence the maximum of the calculated IDFT values (51), the selector (22) also comprising means (54) for selecting the alternative sequence with the lowest maximum (23) for transmission to the receiver (12).

6. A transmitter (10) for transmitting datawords via a multicarrier signal (11) to a receiver (12), the transmitter (10) comprising a generator (20) for generating for each dataword (19) a number of alternative sequences (21), and the transmitter (10) further comprising a selector (22) for selecting the alternative sequence with the lowest peak power value (23) for transmission to the receiver (12), characterized in that the generator (20) is embodied so as to combine mutually different digital words with the dataword (19) in order to form the alternative sequences (21).
7. A transmitter according to Claim 6, characterized in that the generator (20) comprises an augmentor (40) for generating for each dataword (19) a number of intermediate sequences (41) by combining the digital words with the dataword (19), the generator (20) further comprising a scrambler (42) for scrambling the intermediate sequences (41) in order to form the alternative sequences (21).
8. A transmitter according to Claim 7, characterized in that the augmentor (40) is embodied so as to generate for each dataword (19) 2^r intermediate sequences (41) by combining all possible digital words of length r with the dataword (19).
9. A transmitter according to Claim 6, characterized in that the generator (20) comprises a splitter (60) for splitting the dataword (19) and the digital words into fragments (61), the generator (20) further comprising a combiner (62) for combining the fragments (61) in order to form the alternative sequences (21).
10. A transmitter according to any one of Claims 6 to 9, characterized in that the selector (22) comprises an Inverse Discrete Fourier Transformer (50) for calculating for each alternative sequence the Inverse Discrete Fourier Transform (IDFT), the selector (22) further comprising means (52) for determining for each alternative sequence the maximum of the calculated IDFT values (51), the selector (22) also comprising means (54) for selecting the alternative sequence with the lowest maximum (23) for transmission to the receiver (12).
11. A method of transmitting datawords via a multicarrier signal (11) from a transmitter (10) to a receiver (12) comprising the steps of:
- generating for each dataword (19) a number of alternative sequences (21),

- selecting the alternative sequence with the lowest peak power value (23) for transmission to the receiver (12),

characterized in that the step of generating the alternative sequences comprises the step of:

- combining mutually different digital words with the dataword (19) in order to form the alternative sequences (21).

12. A method of transmitting datawords via a multicarrier signal (11) according to Claim 11, characterized in that the step of generating the alternative sequences comprises the steps of:

- generating for each dataword (19) a number of intermediate sequences (41) by combining mutually different digital words with the dataword (19),

- scrambling the intermediate sequences (41) in order to form the alternative sequences (21).

13. A method of transmitting datawords via a multicarrier signal (11) according to Claim 12, characterized in that for each dataword (19) 2^r intermediate sequences (41) are generated by combining all possible digital words of length r with the dataword (19).

14. A method of transmitting datawords via a multicarrier signal (11) according to Claim 11, characterized in that the step of generating the alternative sequences comprises the steps of:

- splitting the dataword (19) and the digital words into fragments (61),

- combining the fragments (61) in order to form the alternative sequences (21).

15. A method of transmitting datawords via a multicarrier signal (11) according to any one of Claims 11 to 14, characterized in that the step of selecting the alternative sequence with the lowest peak power value (23) comprises the steps of:

- calculating for each alternative sequence the Inverse Discrete Fourier Transform (IDFT),

- determining for each alternative sequence the maximum of the calculated IDFT values (51),

- selecting the alternative sequence with the lowest maximum (23) for transmission to the receiver (12).

1/2




FIG. 1




FIG. 2




FIG. 3

2/2




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

national Application No

PCT/EP 00/04196

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L27/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>VAN EETVELT ET AL.: "Peak to average power reduction for OFDM schemes by selective scrambling" ELECTRONICS LETTERS, vol. 32, no. 21, 10 October 1996 (1996-10-10), pages 1963-1964, XP000683518 STEVENAGE, GB ISSN: 0013-5194 page 1964, left-hand column, paragraph 2</p> <p style="text-align: center;">--- -/--</p>	1-3, 5-8, 10-13, 15



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

7 September 2000

Date of mailing of the international search report

14/09/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Scriven, P

INTERNATIONAL SEARCH REPORT

national Application No
PCT/EP 00/04196

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	MÜLLER, HUBER: "A comparison of peak power reduction schemes for OFDM" IEEE GLOBAL TELECOMMUNICATIONS CONFERENCE 3 - 8 November 1997, pages 1-5, XP000737500 New York, US ISBN: 0-7803-4199-6 page 2, left-hand column, paragraph 8 -right-hand column, paragraph 1 page 2, right-hand column, paragraph 4 -page 3, left-hand column, paragraph 3	1,4-6, 9-11,14, 15
X	BÄUML: "Reducing the peak-to-average power ratio of multicarrier modulation by selected mapping" ELECTRONICS LETTERS, vol. 32, no. 22, 24 October 1996 (1996-10-24), pages 2056-2057, XP000643915 STEVENAGE, GB ISSN: 0013-5194 page 2056, line R, paragraph 3	1,5,6, 10,11,15
X	US 5 710 990 A (LONG, LUZ) 20 January 1998 (1998-01-20) column 1, line 38 - line 40 column 1, line 51 - line 59 figure 1	1,5,6, 10,11,15
X	DE 196 35 813 A (HUBER ET AL.) 5 March 1998 (1998-03-05) cited in the application page 3, line 26 - line 31 page 4, line 8 - line 10	1,5,6, 10,11,15
X,P	EP 0 942 566 A (LUCENT) 15 September 1999 (1999-09-15) column 2, line 30 - line 39 column 2, line 45 - line 57 column 3, line 5 - line 16	1,5,6, 10,11,15

INTERNATIONAL SEARCH REPORT

Information on patent family members

national Application No

PCT/EP 00/04196

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5710990	A	20-01-1998	NONE		
DE 19635813	A	05-03-1998	AU 4620197 A		26-03-1998
			CN 1244323 A		09-02-2000
			WO 9810567 A		12-03-1998
			EP 0925672 A		30-06-1999
EP 0942566	A	15-09-1999	JP 11331122 A		30-11-1999

THIS PAGE BLANK (USPTO)